

White Knight Fluid Handling

PPMC300 Ordering Instructions

Required Configurations

PPMC300	CD	-	F	04	E3	-	C1	-	001
	①		②	③	④		⑤		⑥

Bold

= standard option

Please select one option from each of the required fields (1 - 3).

① Liquid Valve Options

① Liquid Valve Type		
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%; padding: 5px;">CD</td> <td style="padding: 5px;">= Spring Loaded Disk Valves</td> </tr> </table>	CD	= Spring Loaded Disk Valves
CD	= Spring Loaded Disk Valves	

② ③ Fitting Style and Size

② Fitting Style	
F	= Flaretek® compatible* <small>*Not available in 1/8"</small>
P	= Pillar S-300®



③ Fitting Size	
02	= 1/8"
04	= 1/4"
06	= 3/8"

④ Electrical Connection

E3	= Turk Connector (Without Cable)
E1	= Wire leads with 5-m (15-ft) ETFE coated cable

⑤ Cycle Rate Control

C1	= Communication Based/Potentiometer
C2*	= Hard Programmed*

*If Option C2 is chosen, option 6 must be added.

⑥ Cycle Rate (Used With Option C2 Only)

001**	= Cycle Rate (Cycles Per Minute)**
--------------	---

**Enter value between 000 and 400 - represents cycles per minute